

LISTING OF THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in this application. Added text is indicated by underlining, and deleted text is indicated by ~~striketrough~~.

1. (Previously presented) A method of transmitting a communication signal between a radio base station and multiple radiation elements, the method comprising:

receiving data signals from multiple radiation elements and producing an input signal adapted to be transmitted over a common feeder cable, wherein the data signals include values representing operating parameters of devices at the multiple radiation elements;

receiving the input signal from the multiple radiation elements over the common feeder cable;

extracting the data signals from the input signal; and

producing a status signal for each device based upon the values representing operating parameters that simulates a feedback signal for the device.

2. (Original) A method as defined in Claim 1, wherein the input signal comprises a plurality of communication signals.

3. (Original) A method as defined in Claim 1, wherein the devices include system cables.

4. (Original) A method as defined in Claim 1, wherein the devices include a mast head amplifier.

Claims 5-7 (Canceled)

8. (Previously presented) A method of transmitting a communication signal between a radio base station and multiple radiation elements, the method comprising:

receiving data signals that include control signals representing operating parameter settings for devices at multiple radiation elements and producing an input signal to be transmitted over a common feeder cable;

receiving the input signal over the common feeder cable;

extracting the data signals from the input signal; and

producing an output signal for each device that transfers the control signals representing operating parameter settings to the device.

9. (Original) A method as defined in Claim 8, wherein the input signal comprises a plurality of communication signals.

10. (Original) A method as defined in Claim 8, wherein the devices include a mast head amplifier.

Application No.: 10/085,340
S. Mellor et al.
Response to Office Action and Request for Reconsideration

Claims 11-14 (Canceled)

15. (Previously presented) An apparatus for transmitting a communication signal between a radio base station and multiple radiation elements, the apparatus comprising:

a bias tee configured to receive an input signal from the multiple radiation elements over a common feeder cable, wherein the input signal comprises data signals that are received from multiple radiation elements and are combined for transmission over the common feeder cable, the data signals including values representing operating parameters of devices at the multiple radiation elements;

a controller configured to extract the data signals from the input signal and to produce a status signal based upon the values representing operating parameters for the devices; and

a load simulator that simulates a feedback signal for the devices in accordance with the status signal.

16. (Canceled)

17. (Previously presented) An apparatus for transmitting a communication signal between a radio base station and multiple radiation elements, the apparatus comprising:

a bias tee configured to receive an input signal over a common cable, wherein the input signal comprises data signals that include control signals

Application No.: 10/085,340

S. Mellor et al.

Response to Office Action and Request for Reconsideration

representing operating parameter settings for devices at multiple radiation elements; and

a controller configured to extract the data signals and to produce an output signal for each device that transfers the control signals representing operating parameter settings to the device.

18. (Canceled)